

3D Culture Systems for a 3D World

RCCS-4SC

Stem Cell



Four Station Rotator Base

Power Supply

(with Tachometer and Ribbon Cable)

Operation Manual

Four Stem Cell Culture Vessels

- Low cost, easy to use system which makes the technology available to most laboratories.
- Four autoclavable Stem Cell type culture vessel of your choice (ImL, 2mL, 4mL or I0mL)
- Sterile valves for vessels and vessel assembly tool included.



FAQ

• How are the cells oxygenated?

In a gas regulated incubator, gas diffuses through the silicone membrane of the bioreactor.

Q: Do the cells stay in one place in the bioreactor?

No, they continuously fall through the media during vessel rotation. The continuous motion of the cells in media facilitates their exposure to nutrients.

Is the RCCS a roller bottle system?

No. Roller bottles grow cells on the wall of the bottle in 2D. The RCCS grows cells in suspension, either as 3D spheroids or on scaffolds/

The Synthecon Rotary Cell Culture System

Produces differentiated high density, three dimensional tissue cultures.

Membrane oxygenation provides bubble free operation, which results in an extremely gentle culture.

Operates in standard incubators. Samples may be easily drawn at any time.

Ideal for growing and maintaining normal tissues, cancer tumors spheroids and bacteria/virally infected tissue models.


Synthecon can design and build systems to user's specifications,

^{*} For additional FAQs visit www.synthecon.com/faq



RCCS-4SC

TECHNICAL SPECIFICATIONS-DIMENSIONS RCCS-4SC **COMPONENT HEIGHT WIDTH** DEPTH 9.0" (22.9 cm) Base 8.0" (20.3 cm) 8.25" (21.0 cm) **Power Supply** 4.5" (11.4 cm) 9.5" (24.1 cm) 9.5" (24.1 cm) **ROTATIONAL COMPONENT WEIGHT SPEED** 7.0 lbs (3.3 Kg) 5-27 RPM Base **Power Supply** 6.0 lbs (2.83Kg)



RCCS-4SC POWER AND ENVIRONMENTAL SPECIFICATIONS			
POWER	VOLTAGE	FREQUENCY	
Power Supply Input	USA 85-260 VAC @ .5Amps	50-60 Hz	
Power Supply Output	7.5 VDC @ 2Amps	50-60 Hz	
ENVIRONMENT	TEMPERATURE	HUMIDITY	
Base	50-105 °F (10-40 °C)	0-100% RH	
Power Supply	50-80 °F (10-27 °C)	0-75% RH	



RCCS-4SC COMPATIBLE CULTURE VESSELS

CULTURE VESSEL MODEL	SIZE	COMPATIBILITY
Disposable HARV *	10 mL	Yes
Disposable HARV *	50mL	Yes
Autoclavable HARV	1 mL	Yes
Autoclavable HARV	2 mL	Yes
Autoclavable HARV	4 mL	Yes
Autoclavable HARV	10 mL	Yes
Autoclavable HARV	50 mL	No
Autoclavable STLV	55 mL	No
Autoclavable STLV	110 mL	No
Autoclavable STLV	250 mL	No
Autoclavable STLV	500 mL	No

^{*} Vessels are supplied four to a pack. Four Stem Cell Autoclavable HARVs are provided with the RCCS-4SC System. All other compatible vessel types are ordered separately. Visit www.synthecon.com for more details.

3D Culture Systems for a 3D World

CellD SARL

19 avenue de l'Aspre 30150 ROQUEMAURE France



0033 4 66 82 82 60 www.celld.com contact-info@celld.com

